

SLIDEWISE MEASURING GUIDE & ORDER FORM



1150 S. 48TH STREET, GRAND FORKS, ND 58201
Phone: 701.746.4519 | **Toll Free:** 877.446.1519
Website: psaccessolutions.com
Email: 4psinfo@psindustries.com

QUOTATION REQUESTED

SLIDEWISE ORDER

SOLD/QUOTE TO:

NAME: _____

COMPANY: _____

ADDRESS: _____

CITY, STATE, ZIP: _____

PHONE: _____ FAX: _____

EMAIL: _____

SHIP TO:

NAME: _____ DATE: _____

ADDRESS: _____ P.O.#: _____

CITY, STATE, ZIP: _____ TAG: _____

PHONE: _____ SHIP VIA: _____

HATCH MODEL/SIZE	HATCH MODEL/SIZE							QTY
	MODEL	OVERALL WIDTH	OVERALL LENGTH	OPENING WIDTH	OPENING LENGTH	MINIMUM SIDE-ROOM	WEIGHT	
SRH-3030A	41"	54"	30"	30"	54"	114 lbs		
SRH-3630A	47"	54"	36"	30"	54"	120 lbs		
SRH-3636A	47"	60"	36"	36"	60"	131 lbs		

Note: Curb must extend a minimum of 3" above roof surface. Maximum curb thickness is 3-1/8" at sides and 2" at front (consult PSI for options if front of curb exceeds 2").

-Put quantity in white table cells.

DEADBOLT:	AVAILABLE OPTIONS:
<input type="checkbox"/> KEYED/ KEYED	<input type="checkbox"/> INSULATED CURB
<input type="checkbox"/> KEYED/ THUMB-TURN	<input type="checkbox"/> SAFETY RAILING SYSTEM

FINISH OPTION	
ALUM	Aluminum

