



CE Marked



Compliant



Controlled / Quiet Operation

SAFEMEZZ360™

THE ALL-ANGLES WAY TO PROTECT YOUR TEAM ON THE MEZZANINE

The SafeMezz360™ is a dual gate system that always keeps a safety gate between an edge and your employee during the important, but potentially hazardous, job of loading and unloading forklifted materials to and from your mezzanine. It meets the most stringent fall protection standards and is arguably the safest material handling gate on the market. Its Slam-Proof™ technology controls speed, reduces noise and provides safety to the operator while the gate is closing. SafeMezz360 is available in single or double pallet widths.

REDUCES ACCIDENTS

- Counter-balanced gate system provides 360 degrees of mezzanine ledge protection
- Slam-Proof™ – a unique damping system provides safety to the operator while the gate is closing, controlling speed, reducing noise and adding life to the gate – all while being mounted high enough to prevent it from becoming damaged
- Side toeboard – Additional toeboard protection at sides of SafeMezz360 assembly

COMPLIES WITH THE MOST STRINGENT STANDARDS



- Meets OSHA 1910.29 Safety Railing Standards
- Meets ANSI standards including the stringent ANSI MH28.3-2009 Section 6.4.3 and ANSI 1264.1-2017 requirements
- Includes ANSI-required 5-inch (127mm) safety toeboard, preventing anything and anyone from falling off the mezzanine edge
- Canadian COHS SOR/94-263, s. 8(F) and SOR/2000-374, s. 2
- ISO 14122-3:2016
- CE Marked

WITHSTANDS TOUGH WORK ENVIRONMENTS

- Constructed with heavy-gauge steel ideal for repetitive use
- Durable, safety yellow powder coat finish

EASY TO INSTALL AND OPERATE

- Easy one-handed operation
- Gate opens and closes smoothly on 2" nylon rollers and track system



Opens And Closes Smoothly While Protecting Workers From The Mezzanine Edge

Slam-Proof™ technology controls closing speed and reduces noise

Industrial-duty chain and sprocket system built for repetitive use

Durable 2" nylon rollers and track system allow for easy, one-handed operation

OSHA- and ANSI-compliant 5" (127mm) safety toeboard

43 5/16" (1100mm) high gate and mid-rail meet OSHA Safety Railing Standards

Bolts easily into place on the mezzanine platform

