VL-580 MEASURING GUIDE Ⅲ PS DOORS Toll Free 877-446-1519 Phone: 701-746-4519 Fax 701-746-8340 MANUFACTURING DIVISION Website: www.psdoors.com CONT. BEAD URETANE SEALANT (TYP BOTH SIDES (A) RMO Width JAMB GASKET LATCH BRACKET FELD WELD TO JAMB LATCH CABLE/ HOOK ASS'Y WATER FORCE WATER FORCE . . ADJUSTABLE PANEL GUIDE BRACKET TRACK HEIGHT/BOTTOM OF BRIDGE O'ALL HEIGHT 37 5/16" (D) CLEAR WALL HEIGHT

RMO HEIGHT

THREADED KNOB TO TIGHTEN LATCH

10 1/8" TRACK DEPTH

GASKET

LIFT POINTS PROVIDED NEAR CENTER FOR

PANEL INSTALLATION

(D) CLEAR WALL HEIGHT

	QUOTE TO:		
	Name:	E-Mail Phone:	
	Company:		
	Address:		
x6 OTHERS)	City:	State:	ZIP:
_GUIDE TRACK (FLUSH WITH OUTSIDE OF JAMB TUBE	PROJECT NAME:	•	
	QUANTITY:		
	DIMENSIONS: (All Measurements in Inches)		
	(A) RMO Width:		
	(B) RMO Height:		
	(C) Panel Height:		
	(D) Clear Wall Height:		
ELECTRIC PERATOR optional)	WATER FORCE:	OPERATOR:	
	☐ Positive Pressure ☐ Reverse Pressure	☐ Electric	☐ Manual
NTERWEIGHT	NOTES:		
/ER SHEETING N			
RUCTURE			
	CUSTOM DRAWINGS If "NO" Approval Dra FOR APPROVAL person "Declining" a		ed, the Name of the must be shown below.
	Yes		
	□ No Name		Date

STEEL COUNTERWEIGHT **UPPER TOWER SHEETING** Product specifications, options, and availability subject to change with out notice. © PS DOORS 2012 Status: Draft Page: 1 of 1

(BY OTHERS)

ELECTRIC OPERATOR

NOT SHOWN TOWER STRUCTURE