HYDRO1-PD522 90 MINUTE FIRE RATED FLOOD DOOR PAIRED MEASURING GUIDE & ORDER FORM



1150 S. 48^{TH} STREET, GRAND FORKS, ND 58201 **Phone:** 701.746.4519 | **Toll Free:** 877.446.1519

Website: psfloodbarriers.com **Email:** 4psinfo@psindustries.com

SWING DIRECTION: C = Keyed Side of Door	.
LHR RHR	ı, Max
VISION LITE OPTIONS: (Viewable Opening Size Shown) None 10"x10" 5"x20" Centered Offset	ROUGH OPENING HEIGHT Door Panel (+) 2 1/4 " DOOR PANEL HEIGHT LOOP PANEL HEIGHT
	SIDE VIEW
ROUGH OPENING WIDT Door Panel (+) 4 ½ Max Frame Depth LEFT PANEL DOOR PANEL WIDTH (Or	n Nax RIGHT PANEL -
Positive Water Force Only TOP VIEW	

SOLD/QUOTE TO:				
NAME:				
COMPANY:				
ADDRESS:				
CITY, STATE, ZIP:				
PHONE:		FAX:		
EMAIL:				
PROJECT INFO:				
PROJECT NAME:				
OPENING NAME:			QUANTITY:	
WATER PROTECTION HEIGHT:	(inches)	LOADING REQUI	RED:	
HYDRODYNAMIC: (FPS)	(PSF)	IMPACT:	(LBS) " X "	
ROUGH OPENING WIDTH:	(inches)	ROUGH OPENIN	G HEIGHT: (inches)	
LEFT PANEL WIDTH:	(inches)	RIGHT PANEL W	IDTH: (inches)	
DOOR PANEL WIDTH:	(inches)	DOOR PANEL HE	EIGHT: (inches)	
ACTIVE PANEL(S):	LATCHING HA	ARDWARE:	VISION LITE: (OPTIONAL)	
LEFT PANEL	PANIC HARD	WARE:	10"x 10"	
RIGHT PANEL				
BOTH PANELS	EXTERIOR TRIM:		5"x 20"	
(SLIDE BOLTS USED ON INACTIVE PANELS)			NONE	
OPENING MATERIAL: VISION LITE LOCATIONS:				
			LEFT PANEL	
	CMU GROUT-FILLED)		DIQUIT DANIEL	
(WALL THICK		(WALL THICKNESS IN INCHES)	RIGHT PANEL	
		iiv iivoriEo)	BOTH PANELS	
DOOR/FRAME MATERIAL:			STANDARDS:	
MILD STEEL (STANDARD)	No. 2b) (MILL FINISH)	1/2" ADA THRESHOLD	
316 STAINLESS STEEL No. 4 (BRUSHED FINISH) CLOSER(S)		CLOSER(S)		
			(INCLUDED ON ACTIVE PANELS)	
TOP COAT PAINT COLOR: (SHERWIN-WILLIAMS INDUSTRIAL ENAMEL)	S/W#	COLOR:	sherwin-williams.com	
STAMPED CALCULATIONS REQUESTED: YES STATE NO				
(Registered professional engineer stamped calculations from within the state or territory the building will be constructed or substantially improved.)				